

4144 Thermal Recorder

SPECIFICATIONS for the 4144:

Number of Channels	1
Channel Width Writing System	40 mm
Frequency Response	DC to 100 Hz at 10 mm (-3 db)
Linearity	± 1% full scale
Hysteresis full scale	± 0.5% full scale
Sensitivity	100 mV/cm; 200 mV/cm; 500 mV/cm; 1 V/cm
Input Impedance	100k ohm (Min.)
Input Circuit	Single ended floating
Operating Voltage	± 12-15 Vdc
Power Consumption	0.4A Typical; 0.6A Maximum
Chart Speeds	25 & 50 mm/sec. standard. For other available speeds, see Options and consult factory.
Chart Paper Capacity	2.125" (54 mm) roll diameter
Size With Electronics	3.80" H x 2.51" W x 4.88" D (9.65cm H x 6.35cm W x 12.40cm D)
Size Without Electronics	3.80" H x 2.51" W x 4.26" D (9.65cm H x 6.35cm W x 10.28cm D)
Weight	1.625 lbs. (737 grams)
Request Outline Drawing Number	MFE 00376260
Options	<ul style="list-style-type: none">- Thermal printhead for alphanumeric annotation in the left hand margin.- DC motor drive for speeds of 5 & 25mm/sec or 10 & 25mm/sec.- Microprocessor based stepper drive for 32 chart speed from 1 mm/hr to 10 mm/sec.- Inverter board for operation from + 12 Vdc supply.



ALLEN DATAGRAPH SYSTEMS, INC.

56 Kendall Pond Road

Derry, NH 03038-4395

Tel: (603)216-6344 Fax: (603) 216-6345

www.allendatagraph.com

